





MultiStations™ |

Reference

324564



QTY	PART NUMBER
3	OS-CABLETRAY10 OS 10" metal cable tray for wire mangement below worksurfaces.
1	OSJP120-43 OS 43" high, clear anodized aluminum hexagonal post with cap.
3	OSJP180-43 OS 43" high, clear anodized aluminum dual function connecting or end post with cap.
3	OSLGP64-A Single 2 1/2" dia. 28 1/2" high steel post leg. Epoxy silver matte powder coat finish to match clear anodized aluminum. 4" square mounting plate. Leg leveller.
6	OSLL12-C OS laminate leg, 12" l x 29" h. Comes with wire management cutout. To be used where two worksurfaces join.
3	OSP4843F14-W2G2 OS Panel, 48" long, 43" high. Laminate 1st tile 29"H, tackboard 2nd tile, 14"H, 2 access grommets, 28"h and grade 2 fabric.
3	OSPD84-4SA-HB 8 wire, 4 circuit, OS Hanging Bracket with Single sided 844SA power module with 4 circuit 15 AMP receptacles (1 with an isolated ground).
1	OSPD84FF36 8 wire, 4 circuit, Metal Flex Connecting Cable 36" Female both ends.
1	OSPD84FF42 8 wire, 4 circuit, Metal Flex Connecting Cable 42" Female both ends.



QTY	PART NUMBER
1	OSPD84SB2-72 8 wire,4 circuit power feed, 72" whip. Branch circuit protection shall be 15 AMP in Canada.
1	OSPD84-SRT Simplex Removal Tool for 84 power delivery system.
3	OSTMTHR-4924-1-SEWO OS Meeting Table half round top, 49"x 24" x 1" with notch out for pos, no grommet.
3	OSW120-4824-SE OS 120° corner worksurface, 28" radius. 48" x 48", 24" side depths. Self edge.Grommet included.
3	PRPS48-00A1-PMGO Privacy Screen, 48 in. long. Frosted Acrylic upper panel, 7 in. high. Panel mounted and no fabric.
3	PRSM161824-N-LFS-CH-C2LO Storage, Mobile, 16L. x 18D. x 24H. Full back. Standard top. File, box combo, horizontal grain. CP Pulls and non locking. No fabric cushion.