





# MultiStations™ |

Reference

324566



QTY	PART NUMBER
8	OS-CABLETRAY10 OS 10" metal cable tray for wire mangement below worksurfaces.
1	OSJP180-43 OS 43" high, clear anodized aluminum dual function connecting or end post with cap.
4	OSJP180-57 OS 57" high, clear anodized aluminum dual function connecting or end post with cap.
2	OSJP90-57 OS 57" high, clear anodized aluminum square post with cap.
2	OSLM24-L OS 24"d worksurface metal ladder leg left with silver finish.
2	OSLM24-R OS 24"d worksurface metal ladder leg right with silver finish.
2	OSP7243F14-W2G2 OS Panel, 72" long, 43" high. Laminate 1st tile 29"H, tackboard 2nd tile, 14"H, 2 access grommets, 28"h and grade 2 fabric.
4	OSP7257L14T14-W0 OS Panel, 72" long, 57" high. Laminate 1st tile 29"H, laminate 2nd tile, 14"H, translucent glass 3rd tile, 14"H, no wire access grommets.
4	OSPD84-4SA-HB 8 wire, 4 circuit, OS Hanging Bracket with Single sided 844SA power module with 4 circuit 15 AMP receptacles (1 with an isolated ground).



QTY	PART NUMBER
-----	-------------

1	<b>OSPD84FF24</b> 8 wire, 4 circuit, Metal Flex Connecting Cable 24" Female both ends.
2	<b>OSPD84FF60</b> 8 wire, 4 circuit, Metal Flex Connecting Cable 60" Female both ends.
2	<b>OSPD84FM60</b> 8 wire, 4 circuit, Metal Flex Connecting Cable 60" Female and Male end.
1	<b>OSPD84SB2-72</b> 8 wire, 4 circuit power feed, 72" whip. Branch circuit protection shall be 15 AMP in Canada.
1	<b>OSPD84-SRT</b> Simplex Removal Tool for 84 power delivery system.
2	<b>OSSB721414S1-1</b> Shared storage, panel mounted, 72w x 14h x 14d. Two sided bin open shelf and laminate backs.
4	<b>OSSP161828-BS-FH</b> OS Pedestal, 15" wide, full height, 2 file drawers. Legal/Letter file bars, lock. No base plate. For use under any depth desk.
2	<b>OSWC72362424-RRSE</b> Worksurface, corner, 72Lx 36D. 24" side depths. 24" main, radius corner, extended right. 1mm edge. Includes universal connecting hardware. Grommets included.
2	<b>OSWC72362424-SRSE</b> Worksurface, corner, 72Lx 36D. 24" side depths. 24" main, straight corner, extended right. 1mm edge. Includes universal connecting hardware. Grommets included.
2	<b>OSWR3624-SEWL</b> Worksurface, rectangular, 36Lx 24D. 1mm edge, grommet in left corner. Includes universal connecting hardware.
2	<b>OSWR3624-SEWR</b> Worksurface, rectangular, 36Lx 24D. 1mm edge, grommet in right corner. Includes universal connecting hardware.